



PA-1242

Order No.: 17.2780

Price upon request

PRODUCTINFOS

Mono PA power amplifier

- 1 x 240 W
- Switchable 400 Hz high-pass filter 6 dB/oct.
- Temperature-controlled fan, continuously adjustable
- LED indication for clip, protect, overtemperature and output level
- Feed-through output (link)
- Mains operation or 24 V emergency power operation

TECHNICAL SPECIFICATIONS

PA-1242

Power rating	240 W
Power rating at 8 Ω	1 x 240 W
Power rating at 100 V	1 x 240 W
Output impedance	25 V/2.6 Ω, 70 V/20 Ω, 100 V/42 Ω, 8 Ω
Channels	1
Inputs	1.2 V
Frequency range	35-20,000 Hz
S/N ratio	> 100 dBA
THD	< 1%

PA-1242

Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	750 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 20 A
Admiss. ambient temp.	0-40 °C
Width	483 mm
Height	88 mm
Depth	374 mm
Rack spaces, RS	2
Weight	12.5 kg
Connections	inputs: XLR, bal. speakers: screw terminals