



# STA-125

Order No.: 25.7250

**Price upon request**

## PRODUCTINFOS

### 2-channel amplifier, 200 W

- Silent operation due to fanless cooling concept
- 2 level controls
- Speaker switch-on delay
- Protected against short circuit and overheating
- LEDs for indicating overload (clip)
- RCA jacks and XLR jacks as stereo inputs, SPEAKER terminals and spring-loaded speaker terminals as stereo outputs

## TECHNICAL SPECIFICATIONS

### STA-125

Peak output power	250 W
Power rating	200 W
Power rating at 4 $\Omega$	2 x 100 W
Power rating at 8 $\Omega$	2 x 80 W
Channels	2
Inputs	500 mV/23 k $\Omega$ (XLR, bal.) 1 V/17 k $\Omega$ (RCA)
Frequency range	20-20,000 Hz

**STA-125**

S/N ratio	> 70 dB
THD	< 0.01%
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	400 VA
Admiss. ambient temp.	0-40 °C
Width	482 mm
Height	88 mm
Depth	220 mm
Rack spaces, RS	2
Weight	7.6 kg
Connections	1 x 3-pole XLR L/R
	1 x RCA L/R
	1 x SPEAKER L/R
	1 x spring-load. speaker term. L/R