



## STA-1504

Order No.: 0244280

### PRODUCTINFOS

#### 4-channel PA amplifier,

with integrated limiter.

- Balanced inputs
- High-pass filter, low-pass filter, can be activated as required for each channel
- Tamper-resistant level adjustment on the rear panel
- 8 Ω bridged operation possible
- LED VU meter and LED per channel for indicating overload (clip)
- Soft start
- Ground lift switch
- Speaker switch-on delay
- Fan cooling
- Protected against short circuit, overheating and DC voltage overlay at the outputs

### TECHNICAL SPECIFICATIONS

#### STA-1504

Peak output power	900 W
Power rating	640 W
Power rating at 4 Ω	4 x 160 W

**STA-1504**

Power rating at 8 $\Omega$	4 x 100 W
Power rating with 8 $\Omega$ bridged operation	2 x 320 W
Channels	4
Inputs	0.7 V/20 k $\Omega$
Frequency range	12-20,000 Hz
Crossover network	yes
Crossover frequency	240 Hz
Integrated limiter	yes
S/N ratio	> 80 dB
Crosstalk attenuation	> 60 dB
THD	< 0.1%
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	1,200 VA
Admiss. ambient temp.	0-40 °C
Width	482 mm
Height	132 mm
Depth	310 mm
Rack units, RU	3
Weight	14 kg
Connections	4 x 3-pole XLR, bal. 4 x screw terminal
Packing dimensions (W x H x L)	0.43 x 0.23 x 0.51 m
Gross weight	15.84 kg
Net weight	14.6 kg