



PA-1200

Order No.: 0170710

PRODUCTINFOS

4-zone mono PA mixing amplifier

- 1 x 120 W
- Silent operation due to fanless cooling concept
- Chime, continuous sound and wailing sound, automatic mute, chime can also be activated via external momentary push-button, 2-tone chime or 4-tone chime (selectable)
- Bass, treble and master controls, level display via LEDs
- 15 V phantom power for channels 2 and 3
- Insertions for various functions are available at option
- 482 mm (19") rack installation with mounting frame PA-1200RM, available at option
- Mains operation and 24 V emergency power operation

TECHNICAL SPECIFICATIONS

PA-1200

| | |
|-------------------|-------|
| Peak output power | 170 W |
| Power rating | 120 W |
| Channels | 5 |
| Zones | 4 |

PA-1200

| | |
|--|--|
| Inputs | 1.5 mV/600 Ω (mic), 150 mV/47 k Ω (line), 1 mV/47 k Ω (phono) |
| Frequency range | 80-15,000 Hz |
| Equalizer bass | \pm 10 dB/100 Hz |
| Equalizer treble | \pm 10 dB/10 kHz |
| S/N ratio | > 60 dB (mic), > 70 dB (line) |
| THD | < 1% |
| Phantom power | 15 V |
| Mains voltage | \sim 230 V |
| Mains frequency | 50 Hz |
| Power consumption, operation | 280 VA |
| Operating voltage (possible alternative) | DC 24 V |
| Power supply (possible alternative) | DC 11 A |
| Admiss. ambient temp. | 0-40 $^{\circ}$ C |
| Width | 420 mm |
| Height | 122 mm |
| Depth | 350 mm |
| Weight | 12.28 kg |
| Connections | 1 x 6.3 mm jack (mic input), 3 x XLR, bal. (mic/line inputs), 1 x RCA L + R (line input), 1 x RCA L + R (phono/line input), spring-load. contact (telephone input), spring-load. contact (tuner output), spring-load. contact (chime button), screw contacts (speakers) |
| Packing dimensions (W x H x L) | 0.47 x 0.2 x 0.52 m |
| Gross weight | 13.8 kg |
| Net weight | 12.28 kg |