



PA-312DMP

Order No.: 17.2980

Price upon request

PRODUCTINFOS

5-zone mono PA mixing amplifier,

with integrated MP3 player.

- 1 x 120 W
- Adjustable MP3 player with USB interface, illuminated display, supplied with remote control
- Autostart function (after switching on the amplifier, the MP3 player starts with the last played song)
- 5 zones, can be switched individually
- 1 unbalanced microphone input
- 2 balanced microphone inputs, can optionally also be used as line inputs
- 2 aux inputs
- 1 emergency input with adjustable automatic talkover
- Speaker outputs via screw terminals
- 1 line output
- Input and output level controls
- 2-way tone control for the output
- 48 V phantom power supply for channels 2 and 3, can be activated as required
- 482 mm (19") rack installation

TECHNICAL SPECIFICATIONS

PA-312DMP

Peak output power

160 W

PA-312DMP

Power rating	120 W
Channels	5
Zones	5
Inputs	5 mV/600 Ω (XLR, bal., mic), 2.5 mV/2 k Ω (6.3 mm jack, mic), 775 mV/10 k Ω (line), 350 mV/10 k Ω (aux), 775 mV/10 k Ω (EMC, telephone)
Frequency range	50-16,000 Hz
Equalizer bass	\pm 10 dB/100 Hz
Equalizer treble	\pm 10 dB/10 kHz
S/N ratio	66 dB (mic) 80 dB (aux)
THD	< 0.5%
Mains voltage	\sim 230 V
Mains frequency	50 Hz
Power consumption, operation	420 VA
Admiss. ambient temp.	0-40 $^{\circ}$ C
Width	482 mm
Height	88 mm
Depth	335 mm
Rack spaces, RS	2
Weight	9.2 kg
Connections	1 x 6.3 mm jack (mic 1) 2 x 6.3 mm jack, 2 x XLR (mic 2-3) 2 x RCA L/R (line 2-3), 2 x RCA L/R (aux 1-2), screw terminals (emergency), 2 x RCA L/R (mix out)