



SIP-MIC

Order No.: 0176410

PRODUCTINFOS

SIP Microphone Station from 2N®

With SIP technology and various functions, e.g. transmission into 12 zones, two-way communication thanks to built-in speaker or reproduction of pre-recorded announcements. Each of the stated functions is available without a server and there is no limitation as to the distance.

SIP microphone station

- For transmitting live audio announcements or previously stored messages into different zones
- Connection to the existing LAN/WAN network
- Connection facility for external microphone, CD/MP3 player or headphones
- 14 buttons, 12 of them to be programmed as required
- Supports IP PBX (SIP)
- Ethernet via RJ45, 10/100 Mbps
- 2 speakers (2 x 1 W)
- 2 logical inputs for contact or voltage of 5-48 V
- Relay output NO/NC, max. 48 V/1 A
- Audio output, 3.5 mm jack
- Main microphone input, balanced, XLR, integrated 24 V phantom power
- Microphone input, 3.5 mm jack

- Line input, 3.5 mm jack
- Power supply via PoE (IEEE 802.3af) or external power supply (12-32 V/1 A)
- Matching power supply PSS-1230DC is available at option

TECHNICAL SPECIFICATIONS

SIP-MIC

Description	SIP microphone station
Nominal value	2 x 1 W speaker
Type	SIP
Power supply	PoE or DC 12-32 V/1 A via external power supply
Dimensions	209 x 65 x 143 mm
Weight	1.25 kg
Connections	RJ45 (LAN), XLR, bal. (microphone), 3.5 mm jack (microphone), 3.5 mm jack (line in)
Other features	SIP
Packing unit	1
Packing dimensions (W x H x L)	0.17 x 0.16 x 0.32 m
Gross weight	1.54 kg
Net weight	1.255 kg

SIP-MIC

Audio Codecs	G.711u, G.722
PoE	IEEE 802.3af
LAN	RJ45, 10/100BASE-TX