



@udinate - Dante

# ADP-DAO-0X2

Order No.: 0259680

### **PRODUCTINFOS**

### Dante® analogue output adapter (2-channel)

- For connecting analogue audio line level devices (e.g. active speakers) to a Dante® audio network
- Adjustable signal level: +18/+4/0 dBu, 0/-10 dBV (via Dante<sup>®</sup> controller)
- Frequency range: 20-20,000 Hz
- Impedance: 150 k $\Omega$  (bal.), 75 k $\Omega$  (unbal.)
- Dynamic range: > 100 dB
- S/N ratio: > 100 dB
- THD: < 0.01%
- Sampling rates: 44.1/48/96 kHz, 24 bits
- Connections: 1 x RJ45, 2 x XLR plug

The brand Dante<sup>®</sup> as well as the Dante<sup>®</sup> software which may have been integrated into these products are licenced by Audinate Pty Ltd.



## **TECHNICAL SPECIFICATIONS**

#### ADP-DAO-0X2

Description Dante® analogue output adapter

Type 2-channel

Colour black
Power supply PoE
Weight 165 g

1 x RJ45,

Connections

2 x 3-pole XLR plug

Packing unit 1

Packing dimensions (W x H x L)  $0.035 \times 0.085 \times 0.2 \text{ m}$ 

Gross weight 0.195 kg
Net weight 0.165 kg

ADP-DAO-0X2

Sampling rates 44.1/48/96 kHz

Resolution 24 Bit