



## RDA20



Order No.: 1001172

### PRODUCTINFOS

#### Active speaker with integrated Dante® module

- Self-amplified speaker system, addressable via Dante® audio network
- Supports PoE/PoE+ Ethernet audio connection and power supply via RJ45 connection
- Output power: 10 W with PoE, 20 W with PoE+
- Supplied with 2 wall brackets
- Automatic assignment of an IP address via DHCP router
- Relacart speaker management software for easy setup and remote management

System requirements Dante®: Windows 7/8.1/10/11 or MacOS 10.9.5/10.10.5/10.11

The brand Dante® as well as the Dante® software which may have been integrated into these products are licenced by Audinate Pty Ltd

**Please note: RELACART products are distributed by MONACOR INTERNATIONAL exclusively in the following countries: Germany, Austria, Switzerland, Netherlands, Belgium, Luxembourg, Denmark, Portugal, Malta. Orders from other countries cannot be fulfilled.**

**Manufacturer information:**

Relacart Electronics Co., Ltd.  
1408 Room, B Building  
Fengxing Plaza  
No. 242, Tianhe Road  
Tianhe District  
Guangzhou, Guangdong  
China  
info@relacart.com

**Importer:**

MONACOR INTERNATIONAL GmbH & Co. KG  
Konsul-Smidt-Str. 68  
28217 Bremen  
Germany  
info@monacor.com

**Safety Notes and Warning Messages**

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Never adjust the speakers to a very high volume. Permanent high volumes may damage your hearing!

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

**TECHNICAL SPECIFICATIONS****RDA20**

Active/passive	active
Transmission technology	Dante <sup>®</sup>
Total output power	30 W
Power rating (RMS)	10 W (PoE), 20 W (PoE+)
Frequency range	85-17,000 Hz
System	2-way
Bass speaker	10 cm (4") cone speaker
Tweeter	7.6 cm (3") cone tweeter
Number of speakers	2
Speaker size	10 cm (4")
SPL	96 dB/W/m

**RDA20**

Max. rated SPL	110 dB
Radiation angle/beam angle	90°
Radiation angle, horizontal	90°
Radiation angle, vertical	90°
Housing material	wood, protective metal grille
Colour	white
Mounting device	wall bracket
Power supply	37-57 V PoE/PoE+ via RJ45
Dimensions	132 x 235 x 142 mm
Width	132 mm
Height	235 mm
Depth	142 mm
Weight	2.36 kg
Inputs	1 x RJ45 (Dante® IN)
Other features	integr. DSP for tone control via software
Packaging dimensions (W x H x L)	0.205 x 0.33 x 0.215 m
Gross weight	2.95 kg
Net weight	2.36 kg

**RDA20**

EAN code	4007754426700
Net weight	2.36 kg