



SPEECH-204

Order No.: 0179130

PRODUCTINFOS

Set up, connect and go: audio lectern for multimedia presentations

The SPEECH-204 is an efficient and portable lectern with built-in mixing amplifier and integrated speaker system in 2-way technology. The elaborate functionality and high sound quality ensure a successful and professional performance and thus contribute to the success of every event. The SPEECH-204 is set up and ready for use in no time and ideally suited for multimedia presentations in hotels, houses of worship, conference rooms and convention centres.

Professional lectern with integrated 2-channel multifrequency receiver unit with UHF PLL technology

- Built-in high-performance mixing amplifier and speaker system, 75 W
- 2 x 16 selectable UHF frequencies (863.1-864.9 MHz)
- Integrated limiter
- 3 inputs via comb. jack mic (XLR)/line (6.3 mm jack) with 3-way equalizer and gain control
- 1 stereo line input via RCA jacks with gain control
- 2 shock-absorbing XLR jacks on the top part of the lectern for 2 optional gooseneck microphones (use one microphone input each), with 24 V phantom power
- 1 stereo line output via RCA jacks
- 2-way speaker system

- Integrated light in the top part of the lectern
- Column with 2 document compartments and 2 storage compartments
- 2 castors

Supplied w/o gooseneck microphone. Matching microphone EMG-650P is available at option.

Matching microphone transmitters or pocket transmitters are available at option, e.g. TXA-800HSE or TXA-800HT.

Licence-free in the EU.

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Warning and Safety Instructions

The device is supplied with dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Risk of electric shock!

Do not use this device and disconnect it immediately from the power supply if the device or the power supply cable is visibly damaged, if a defect might have occurred after the device was dropped or suffered a similar accident, if malfunctions occur. Any repairs must be carried out by specialists.

The product is suitable for indoor use only. Protect it against dripping water, splash water and high air humidity (admissible ambient temperature range is 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

The heat generated in the device must be dissipated by air circulation. Never cover the air vents of the housing.

If the device is to be put out of operation definitely, dispose of the product in accordance with local regulations.

TECHNICAL SPECIFICATIONS

SPEECH-204

Rated power (P_{RMS})	75 W
Peak output power	100 W
Frequency range	60-20,000 Hz

SPEECH-204

Carrier frequency	863.1-864.9 MHz
Operating range	≈ 25 m
Inputs	15 mV (mic 1), 5 mV (mic 2-3), 220 mV (line 1-3), 250 mV (line)
Max. SPL	113 dB
Equalizer, bass	±12 dB/60 Hz
Equalizer, midrange	±7 dB/1 kHz
Equalizer, treble	±12 dB/15 kHz
Power supply	~ 230 V/50 Hz/180 VA
Admiss. ambient temp.	0-40 °C
Dimensions	540 x 1140 x 430 mm
Weight	33 kg
Connections	3 x XLR (mic), 3 x 6.3 mm jack (line), 1 x RCA L/R (line in), 1 x RCA L/R (line out)

SPEECH-204

EAN code	4007754270358
Net weight	35.96 kg