



## ATS-22R

Order No.: 0257110

### PRODUCTINFOS

#### 16-channel Digital Voice Transmission System, 863-865 MHz

- Suitable as a tour guide system, trainer/student system and for any other application in which a certain voice source is to be distributed to one or more receivers
- High resistance to interference due to digital transmission
- Parallel operation of up to 4 different channels possible without any interference
- Licence-free in the EU

#### 16-channel miniature receiver,

with intercom function.

- Intercom function with transmitter ATS-22T via push-button
- Built-in microphone
- Supplied with matching clip-on earphone
- Switches off automatically after not receiving an input signal for 20 minutes (power-saving function)
- LCD for indicating channel, carrier signal, volume and battery status
- Power supply via integrated rech. lithium battery (3.7 V/600 mAh)
- Micro USB charging connection for ATS-12CB, ATS-35CB or USB charger, available at option

- Dimensions: 40 x 87 x 12 mm

**Licence-free in the EU.**

## TECHNICAL SPECIFICATIONS

### ATS-22R

#### General information

Description	16-channel digital miniature receiver
Carrier frequency range	863-865 MHz
Channels	1
Operating time	> 15 h
Admiss. ambient temp.	0-40 °C

#### Specifications receiver

Power supply receiver	integrated rech. lithium batt. (3.7 V/600 mAh)
Width receiver	40 mm
Height receiver	87 mm
Depth receiver	12 mm
Weight receiver	37 g
Connections receiver	3.5 mm jack (earphone), micro USB charging port

### ATS-22R

EAN code	4007754246230
Net weight	0.052 kg