



ATS-22T

Order No.: 25.7120

Price upon request

PRODUCTINFOS

16-channel Digital Voice Transmission System, 863-865 MHz

- Suitable as a tour guide system, trainer/student system and for any other application in which a certain voice source is to be distributed to one or more receivers
- High resistance to interference due to digital transmission
- Parallel operation of up to 4 different channels possible without any interference
- Licence-free in the EU

16-channel miniature transmitter,

for microphone operation and audio line signals, with intercom function.

- Supplied with headset
- Activation switch for intercom function with the receiver ATS-22R
- Audio line input via 3.5 mm jack at the headset
- LCD for indicating channel and battery status
- Mute button
- Transmitting power: ≤ 10 mW (EIRP), operating range: approx. 70 m

- Power supply via integrated rech. lithium battery (3.7 V/600 mAh)
- Micro USB charging connection for ATS-12CB, ATS-35CB or USB charger, available at option
- Dimensions: 40 x 80 x 12 mm
- Weight: 37 g

Licence-free in the EU.

TECHNICAL SPECIFICATIONS

ATS-22T

General information

Description	-
Description	16-channel digital miniature transmitter
Carrier frequency range	863-865 MHz
Admiss. ambient temp.	0-40 °C

Specifications transmitter

Transmitting power	≤ 10 mW
Operating range	70 m
Power supply transmitter	integrated rech. lithium batt. (3.7 V/600 mAh)
Width transmitter	40 mm
Height transmitter	80 mm
Depth transmitter	12 mm
Weight transmitter	37 g
Connections transmitter	3.5 mm jack (microphone/line in), micro USB charging port