



ATS-50T

Order No.: 0255170

Price upon request

PRODUCTINFOS

40-channel Mono PLL Voice Transmission System, 863-865 MHz

- Economy tour guide system
- Due to the narrow-band frequency range which has been perfectly adapted to voice transmissions, a parallel operation of up to 12 different channels is possible without any interference
- Licence-free in the EU

40-channel PLL transmitter,

for microphone operation and audio line signals.

- Integrated microphone
- Supplied with additional electret tie clip microphone
- Audio line input via 3.5 mm stereo jack
- LCD for indicating channel and battery status
- Mute button
- Belt clip
- Transmitting power: ≤ 10 mW (EIRP), operating range: approx. 110 m

- Power supply via 1 x 1.2 V NiMH rech. battery AA size (not supplied)
- Dimensions: 42 x 98 x 24 mm
- Weight: 42 g

Licence-free in the EU.

TECHNICAL SPECIFICATIONS

ATS-50T

General information

Description	-
Description	40-channel mono PLL transmitter
Carrier frequency range	863-865 MHz
Admiss. ambient temp.	0-40 °C

Specifications transmitter -

Transmitting power	≤ 10 mW
Operating range	110 m
Power supply transmitter	1 x 1.2 V NiMH rech. batt. AA size
Width transmitter	42 mm
Height transmitter	98 mm
Depth transmitter	24 mm
Weight transmitter	42 g
Connections transmitter	3.5 mm jack (microphone), 3.5 mm jack (line in)