



TXA-802SR

Order No.: 17.2990

Price upon request

PRODUCTINFOS

Professional 16-channel Mono PLL Audio Transmission System, 863-865 MHz, with Extensive Accessories

- Compatible with portable amplifier systems of the TXA-800 and TXA-1020 series
- Can be combined with the TXA-800 and TXA-1020 series, but also suitable as a tour guide system and for any other application in which a certain audio source or voice source is to be distributed to one or more receivers
- Can be combined with transmitters and receivers of the ATS-16 series
- Simultaneous operation of up to 4 transmitters with different frequencies (dep. on distance of transmitters, stationary RF sources of interference and other local conditions)
- Licence-free in the EU

2-channel multifrequency receiver,

with UHF PLL technology.

- Matching the transmitters TXA-800HT, TXA-800HSE, TXA-800ST and ATS-12HT
- 2 x 16 selectable UHF frequencies (863.1-864.9 MHz) with diversity system

- Scan function for free channel
- Volume control
- LCD for indicating selected channel and carrier signal
- Balanced XLR output and 6.3 mm jack output
- 482 mm (19") rack installation of 2 devices is possible with supplied mounting brackets
- Power is provided via enclosed plug-in power supply
- Dimensions: 215 x 50 x 210 mm
- Weight: 1.2 kg

Licence-free in the EU.

TECHNICAL SPECIFICATIONS

TXA-802SR

General information

Description	- receiver unit
Carrier frequency range	863.1-864.9 MHz
Channels	2
Admiss. ambient temp.	0-40 °C

Specifications receiver

	-
Audio signal receiver	30 mV (XLR), 730 mV (6.3 mm jack, high), 80 mV (6.3 mm jack, low)
Power supply receiver	via encl. plug-in power supply
Width receiver	215 mm
Height receiver	50 mm
Depth receiver	210 mm
Weight receiver	1.2 kg
Connections receiver	1 x XLR, bal., 1 x 6.3 mm jack, unbal.