



ECM-306BU/SW

Order No.: 0237270

PRODUCTINFOS

USB boundary microphone

- For operating directly at a PC or laptop
- No driver installation required, device will be identified automatically
- Integrated A/D converter: 48 kHz/16 bits
- Power LED
- Additional headphone connection: 3.5 mm jack
- 1.2 m connection cable with micro USB/USB Type-A plug
- Rear cutout for fixed installation (e.g. wall mounting)

Especially suitable for the use as a desktop microphone!

TECHNICAL SPECIFICATIONS

ECM-306BU/SW

Description	boundary microphone
Version	USB
Transmission method	cable
Polar pattern	semi-cardioid
System	electret

ECM-306BU/SW

Audio frequency range	50-18,000 Hz
Sensitivity	3.2 mV/Pa
S/N ratio	55 dB
Max. sound pressure	110 dB
Power supply	DC 5 V via USB interface
Admiss. ambient temp.	0-40 °C
Dimensions	90 x 25 x 90 mm
Weight	187 g
Cable	1.2 m
Connection	micro USB/USB Type-A plug
Packing dimensions (W x H x L)	0.187 x 0.1455 x 0.057 m
Gross weight	0.38 kg
Net weight	0.225 kg

ECM-306BU/SW

Sampling rates	48 kHz
Resolution	16 Bit