



## HSE-110

Order No.: 0232170

### PRODUCTINFOS

#### Headband microphone

- High-quality back electret cartridge
- Very linear frequency response, especially resistant to external sound due to its supercardioid characteristic with high back suppression
- The power supply adapter EMA-1 or a respective power supply is required for operation
- 3-pole mini XLR inline jack, matching EMA-1 or a pocket transmitter TXS-...HSE

### TECHNICAL SPECIFICATIONS

#### HSE-110

|                       |                     |
|-----------------------|---------------------|
| Description           | headband microphone |
| Transmission method   | cable               |
| Polar pattern         | supercardioid       |
| System                | back electret       |
| Audio frequency range | 20-20,000 Hz        |
| Nominal impedance     | 3 k $\Omega$        |

**HSE-110**

|                                |                         |
|--------------------------------|-------------------------|
| Sensitivity                    | 7 mV/Pa                 |
| Max. sound pressure            | 120 dB                  |
| Power supply                   | DC 1.3-20 V             |
| Admiss. ambient temp.          | 0-40 °C                 |
| Weight                         | 69 g                    |
| Connection                     | 3-pole mini XLR         |
| Packing dimensions (W x H x L) | 0.175 x 0.055 x 0.215 m |
| Gross weight                   | 0.207 kg                |
| Net weight                     | 0.069 kg                |