

HSE-340/SK - Page: 1



## HSE-340/SK

Order No.: 1000026

## **PRODUCTINFOS**

## Professional headband microphone,

with cardioid polar pattern and a high-quality sound which is suitable for any vocal or speech application. Innovative design features ensure a maximum suppression of both the impact sound and structure-borne noise as well as an extra low acoustic feedback, very comfortable to wear. Beige version.

- Corrosion-resistant neckband, easy to clean
- Drip ring (protects cartridge from moisture)
- Unobtrusive and secure fit due to cable routing in neck area incl. strain relief and cable bending protection
- Stable positioning
- Microphone windshield
- 4-pole mini XLR inline jack for connection to pocket transmitters from JTS or a pocket transmitters of the same design from other brand manufacturers

## **TECHNICAL SPECIFICATIONS**

HSE-340/SK - Page: 2

| HSE-340/SK            |                              |
|-----------------------|------------------------------|
| Description           | headband microphone          |
| Transmission method   | cable                        |
| Polar pattern         | cardioid                     |
| System                | electret                     |
| Audio frequency range | 50-18,000 Hz                 |
| Nominal impedance     | 2 kΩ                         |
| Sensitivity           | 2.3 mV/Pa                    |
| Max. sound pressure   | 120 dB                       |
| Power supply          | 1.5-9 V                      |
| Admiss. ambient temp. | 0-40 °C                      |
| Weight                | 18 g (w/o cable<br>and plug) |
| Connection            | 4-pole mini XLR              |
| Gross weight          | 0.208 kg                     |
| Net weight            | 0.037 kg                     |