



MPX-52PA

Order No.: 20.2300

Price upon request

PRODUCTINFOS

2-zone mixer,

for multi-room PA applications.

- 2 independent zones with user-defined routing of all input channels
- 1 microphone way as announcing channel, balanced, with 3-way equalizer and adjustable automatic talkover
- 4 stereo input channels with stereo line inputs and balanced microphone ways
- Channel 1 additionally with a balanced line input, channels 3 and 4 switchable line/phono
- Signal/peak indication for each channel
- Recessed gain control for each input channel
- Zone outputs, balanced, with 3-way equalizer, LED level indication of the stereo master, balance controls, pre-fader listening (PFL) and mono/stereo selection
- Adjustable headphone output with pre-fader listening (PFL) to the stereo input channels and zone outputs
- 2 zone outputs for each stereo RCA and XLR L/R, bal.
- 1 record output for each zone (independent of talkover and announcements)
- Connection for gooseneck light GNL-204

TECHNICAL SPECIFICATIONS

MPX-52PA

No. of channels	6
No. of inputs	13
Mic input	1.5 mV, 5 x 3-pole XLR/6.3 mm jack
Line input	120 mV, 1 x 3-pole XLR L/R, 4 x RCA L/R
Phono input	3 mV, 2 x RCA L/R
Master output	1 V, 2 x 3-pole XLR L/R, 2 x RCA L/R
Record output	550 mV, 2 x RCA L/R
Headphones	≥ 32 Ω, 1 x 6.3 mm jack
Gooseneck lamp	12 V/0.75 W, 1 x BNC
Frequency range	20-20,000 Hz
THD	< 0.1%
S/N ratio	71 dB, unweighted
Equalizer bass	±15 dB/50 Hz
Equalizer midrange	±12 dB/1 kHz
Equalizer treble	±15 dB/10 kHz
Talkover	level attenuation 20 dB max.
Power supply	~ 230 V/50 Hz/15 VA
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	15 VA
Admiss. ambient temp.	0-40 °C
Width	482 mm
Height	138 mm
Depth	190 mm
Rack spaces, RS	3
Weight	3.9 kg