



PA-6040MPX

Order No.: 17.4760

Price upon request

PRODUCTINFOS

4-zone mixer,

for general multi-room PA applications.

- 4 zones with user-defined routing of all input channels
- 4 inputs microphone/line via comb. jacks
- 2 inputs line stereo via RCA jacks
- Each input channel with gain control, 2-way tone control and zone routing switch
- Microphone inputs with phantom power, to be switched on as required
- Independent paging input, can be routed to each zone
- 4 zone outputs, can be adjusted individually
- Monitor output and record output
- Each microphone/line input with connection for external chime button, 2-tone chime or 4-tone chime or siren (selectable)
- Connection for push-to-talk microphone PA-4000PTT
- Optional connection for up to 32 zone paging microphones PA-4000RC
- Level control via zone VU meter
- Mains operation or 24 V emergency power operation

TECHNICAL SPECIFICATIONS

PA-6040MPX

Channels

6

PA-6040MPX

Zones	4
Inputs	2.5 mV/5 k Ω , bal., 250 mV/15 k Ω , bal. (mic/line), 250 mV/15 k Ω (line), 250 mV/10 k Ω (telephone paging)
Frequency range	20-20,000 Hz
Equalizer bass	\pm 10 dB/100 Hz
Equalizer treble	\pm 10 dB/10 kHz
S/N ratio	> 65 dB (mic), > 87 dB (line)
THD	< 1%
Mains voltage	\sim 230 V
Mains frequency	50 Hz
Power consumption, operation	15 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 500 mA
Admiss. ambient temp.	0-40 °C
Width	482 mm
Height	90 mm
Depth	305 mm
Rack spaces, RS	2
Weight	4.4 kg
Connections	4 x combo 6.3 mm/XLR (mic/line), 2 x RCA L/R (line), 4 x 6.3 mm jack (zone inputs), plug-in screw terminal (paging), plug-in screw terminal (chime button), 1 x RJ45 (push-to-talk mic), 4 x XLR (zone outputs), 1 x 6.3 mm jack (monitor), 1