



TX-8220



Order No.: 21.0360

Price upon request

PRODUCTINFOS

Stereo receiver

- Power: 100 W per channel (6 Ω , 1 kHz, 10%, 1 channel controlled, IEC)
- Streaming from mobile devices, smartphones, tablets, laptops and PCs with Bluetooth version 4.1 (A2DP/AVRCP) with Bluetooth standby mode and autoconnect function
- DAB+ and UKW/RDS tuner with 40 station memory
- Labelling radio stations (up to 8 characters)
- WRAT (Wide Range Amplifier Technology) with robust high-current EI transformer and special power capacitors
- Amplifier circuit without phase shift with unobtrusive power transformers
- Optimum Gain Volume Circuitry
- 192 kHz/24 bits (PCM1754) digital/analogue converter
- Direct mode for authentic reproduction of sound source
- 96 kHz/24 bits D/A conversion
- Selection buttons on the front panel for bass/treble/balance
- Selection button on the front panel for selecting speaker A or B
- 3-step dimming for display (normal/dark/darker)
- Sleep timer and battery-free memory
- RI remote control (Remote Interactive) for each function
- Bluetooth standby mode and automatic standby function
- 2 digital audio inputs (1 optical, 1 coaxial)

- 4 analogue RCA inputs and 1 line output
- Phono input and MM equalizer
- Subwoofer preamplifier output
- 2 pairs of speaker screw terminals
- 6.3 mm headphone jack
- Dimensions: 435 x 149 x 328 mm
- Weight: 7 kg

TECHNICAL SPECIFICATIONS

TX-8220

Power rating	2 x 100 W/6 Ω
Channels	2
Inputs	450 mV/40 k Ω (line), 10 mV/50 k Ω (phono)
Frequency range	10-100,000 Hz
Equalizer bass	± 12 dB/100 Hz
Equalizer treble	± 12 dB/10 kHz
S/N ratio	100/93 dB
THD	0.08%
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	20 W
Power consumption, standby	0.4 W
Admiss. ambient temp.	0-40 $^{\circ}$ C
Width	435 mm
Height	149 mm
Depth	328 mm
Weight	7 kg
Connections	4 x RCA L/R (line in), 1 x RCA L/R (phono), 1 x RCA, 1 x Toslink (digital in), 1 x RCA L/R (line out), 1 x RCA (subwoofer), 1 x 6.3 mm jack (headphones), 4 x speaker terminal (speakers)