



TXB-602/SW

Order No.: 0130050

PRODUCTINFOS

Speaker system, 50 W, 4 Ω ,

suitable for portable amplifier systems TXA-604/SW and TXA-624CD/SW.

- Cabinet with durable two-component PU coating
- 2-way bass-reflex speaker system
- Excellent sound characteristics due to a 20 cm (8", FAITAL) bass speaker and 25 mm (1") horn tweeter
- Frequency range: 60-18,500 Hz
- SPEAKON connection
- Stand sleeve
- Supplied with practical protective shoulder bag which can stay on during operation
- Dimensions: 240 x 400 x 290 mm
- Weight: 8.2 kg

TECHNICAL SPECIFICATIONS

TXB-602/SW

Active/passive

passive

TXB-602/SW

Power rating (RMS)	50 W
Impedance	4 Ω
Frequency range	60-18,500 Hz
System	2-way bass-reflex
Bass speaker	20 cm (8", Faital)
Tweeter	25 mm (1") horn
Number of speakers	2
Speaker size	20 cm (8")
Housing material	birch plywood/wood
Colour	black
Mounting device	stand sleeve
Admiss. ambient temp.	0-40 °C
Dimensions	240 x 400 x 290 mm
Width	240 mm
Height	400 mm
Depth	290 mm
Weight	8.18 kg
Inputs	NEUTRIK SPEAKON
Packing dimensions (W x H x L)	0.32 x 0.5 x 0.36 m
Gross weight	9.32 kg
Net weight	8.18 kg