



# PA-1200M

Order No.: 0240260

## PRODUCTINFOS

### Monitor unit, 10 + 1 channels

- Audio sources can be selected via rotary switch
- 10 monitor inputs 1-100 V/10 k $\Omega$
- 1 aux input 0 dB (0.775 V)/600  $\Omega$
- Level control, LED VU meter and clip LED for each monitor input
- Built-in 2 W speaker, volume control
- Headphone output
- Mains operation and 24 V emergency power operation

## TECHNICAL SPECIFICATIONS

### PA-1200M

Power rating	2 W
Channels	11
Inputs	1-100 V/10 k $\Omega$ (monitor) 0.775 V/600 $\Omega$ (aux)
Frequency range	100-20,000 Hz
THD	< 0.3%
Mains voltage	DC 230 V
Mains frequency	50 Hz
Power consumption, operation	15 VA

**PA-1200M**

Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	0.5 A
Admiss. ambient temp.	0-40 °C
Width	482 mm
Height	88 mm
Depth	200 mm
Rack spaces, RS	2
Weight	4.7 kg
Connections	screw terminals (monitor input 1-10), screw terminals (aux input), 6.3 mm jack (headphones)
Packing dimensions (W x H x L)	0.34 x 0.175 x 0.55 m
Gross weight	5.86 kg
Net weight	4.8 kg