



# MCX-200/SW

Order No.: 24.4170

**Price upon request**

## PRODUCTINFOS

### Electronic stereo crossover network

- Subwoofer operation/satellite operation
- Additional mono subwoofer output
- Output level can be adjusted individually for each frequency range
- Switchable phase for subwoofer output
- Adjustable crossover frequency
- Ground lift switch
- All connections via 6.3 mm jacks, unbal.

## TECHNICAL SPECIFICATIONS

### MCX-200/SW

|                       |                                      |
|-----------------------|--------------------------------------|
| Frequency range       | 10-30,000 Hz, -0.5 dB                |
| Crossover frequency   | 60-500 Hz, 12 dB/oct.                |
| High-pass filter      | 15 Hz, 12 dB/oct.                    |
| THD                   | < 0.03%                              |
| Inputs                | 6 V max./56 k $\Omega$               |
| Outputs               | 6 V max./100 $\Omega$ ( $\pm$ 10 dB) |
| S/N ratio             | > 80 dB                              |
| Power supply          | ~ 230 V/50 Hz/5 VA                   |
| Admiss. ambient temp. | 0-40 °C                              |
| Dimensions            | 482 x 44.5 x 185 mm, 1 RS            |

**MCX-200/SW**

Weight

2 kg