



MDSP-24BAL

Order No.: 11.2350

Price upon request

PRODUCTINFOS

Digital signal processor (DSP),

in an aluminium housing, with 2 analogue inputs and 4 analogue outputs (balanced).

- AD/DA converter, 24 bits
- Sampling rate: 48 kHz
- 2 balanced inputs via screw terminals (0.9 V/2 V, switchable)
- 4 balanced outputs via screw terminals (0.9 V)
- Programming and administration via mini USB interface and control software (Windows* XP/Vista/7, Mac OS X Intel)
- The following parameters can be changed with the control software (supplied with voucher code):
 - Filters: high-shelf, low-shelf, high-pass, low-pass
 - Graphic equalizer
 - Parametric equalizer
 - Matrix mixer
 - Volume, mute, polarity

- Power is provided via optional 12 V power supply (e.g. PSS-1205DC)
- Dimensions: 147 x 45 x 130 mm
- Weight: 362 g

TECHNICAL SPECIFICATIONS

MDSP-24BAL

Description	digital signal processor (DSP)
Input signal	0.9 V/2 V
Output signal	0.9 V
High-pass filter	software
Low cut	software
Admiss. ambient temp.	0-40 °C
Power supply	via optional 12 V power supply
Dimensions	147 x 45 x 130 mm
Weight	362 g
Inputs	screw terminals
Outputs	screw terminals