



SPM-200X/4

Order No.: 0105370

PRODUCTINFOS

Full range speaker, 30 W, 4 Ω

- Sheet steel basket
- Paper cone with dual cone
- Wide frequency response
- High efficiency
- For PA and hi-fi applications
- Subwoofer support required for hi-fi applications

TECHNICAL SPECIFICATIONS

SPM-200X/4

Impedance (Z)	4 Ω
Frequency range	f3-15,000 Hz
Resonant frequency (fs)	89 Hz
Power rating (RMS)	30 W
Peak music power output (MAX)	60 W

SPM-200X/4

SPL	94 dB/W/m
Suspension compl. (Cms)	0.27 mm/N
Moving mass (Mms)	9.9 g
Mech. Q factor (Qms)	2.69
Electr. Q factor (Qes)	1.52
Total Q factor (Qts)	0.97
Equivalent volume (Vas)	14.9 l
DC resistance (Re)	3.7 Ω
Force factor (BxL)	3.90 Tm
Voice coil induct. (Le)	0.2 mH
Voice coil diameter	Ø 25 mm
Voice coil former	aluminium
Linear excursion (X _{MAX})	± 1 mm
Eff. cone area (Sd)	201 cm ²
Magnet weight	229 g
Magnet diameter	Ø 70 mm
Mounting cutout	Ø 184 mm
Mounting depth	76 mm
Mounting hole diameter	Ø 194 mm
Dimensions	Ø 205 mm x 82 mm
Outside diameter	Ø 205 mm
Width	Ø 205 mm
Depth	82 mm
Colour	black
Admiss. ambient temp.	0-40 °C
Weight	0.734 kg
Packing unit	1
Type of speaker	8"
Packing dimensions (W x H x L)	0.22 x 0.11 x 0.22 m
Gross weight	0.9 kg
Net weight	0.734 kg