



## ETS-515TW/SW

Order No.: 0162620

### PRODUCTINFOS

#### PA column speakers

- 100 V line technique or 8  $\Omega$  operation
- 2-way version (with additional integrated tweeter for a clearly improved sound)
- Integrated crossover network
- 6-step power selector switch with 8  $\Omega$  switching
- 2 x 6 mm threaded bushing
- Plastic cabinet and protective metal grille in black (SW) or white (WS)
- Supplied with mounting brackets
- Connection via spring-loaded speaker terminal

### TECHNICAL SPECIFICATIONS

#### ETS-515TW/SW

Active/passive	passive
Transmission method	100 V
Total power rating	30 W

**ETS-515TW/SW**

Power rating (RMS)	15/7.5/4/2/1 W (100 V) 15 W (8 $\Omega$ )
Impedance	8 $\Omega$
Frequency range	90-20,000 Hz
System	2-way
Number of speakers	2+1
Sensitivity	87 dB/W/m
Housing material	plastic
Colour	black
Mounting device	mounting bracket
Admiss. ambient temp.	0-40 °C
Dimensions	128 x 385 x 140 mm
Width	128 mm
Height	385 mm
Depth	140 mm
Weight	2.8 kg
Packing dimensions (W x H x L)	0.18 x 0.18 x 0.51 m
Gross weight	3.1 kg
Net weight	2.84 kg