



ETS-630DT



Order No.: 0163490

PRODUCTINFOS

Active PA column speaker,

with integrated Dante® module.

- 30 W class D amplifier
- 6 x 7.6 cm (3") full range speaker
- Decoding: 16/24/32 bits
- Sampling rates: 44.1/48/88.2/96 kHz
- PoE (Power over Ethernet)
- 2 x M12 threaded bushing
- Metal cabinet with white metal front grille
- Supplied with mounting bracket

System requirements Dante®: Windows 7/8.1/10 or MacOS 10.9.5/10.10.5/10.11

The brand Dante® as well as the Dante® software which may have been integrated into these products are licenced by Audinate Pty Ltd.



TECHNICAL SPECIFICATIONS

ETS-630DT

Active/passive active

Transmission technology Dante®

Power rating (RMS) 30 W

Frequency range 120-18,000 Hz

Input signal Dante®

System full range

Full range speaker 6 x 7.6 cm

Number of speakers 6

 Speaker size
 7.6 cm (3")

 SPL
 95 dB/W/m

 Max. rated SPL
 110 dB

Radiation angle/beam angle H: 120°/V: 40°

Radiation angle, horizontal 120°
Radiation angle, vertical 40°
Housing material metal
Colour white

Mounting device mounting bracket

Admiss. ambient temp. $0-40~^{\circ}\text{C}$ Power supply PoE

Dimensions 95 x 610 x 120 mm

Width 95 mm
Height 610 mm
Depth 120 mm
Weight 5.57 kg
Inputs RJ45

Packing dimensions (W x H x L) 0.18 x 0.205 x 0.72 m

Gross weight 6.32 kg
Net weight 5.57 kg

ETS-630DT

Sampling rates 44.1/48/88.2/96 kHz

Resolution 16/24/32 bits