



TS-C10-300/T



Order No.: 0163740

PRODUCTINFOS

Weatherproof PA column speaker,

with EN 54-24 certification.

- 100 V line technique
- 2 x 7.7 cm (3") waterproof full range speaker
- 4 power taps: 10/6/3/1.5 W
- Connection via ceramic terminals with thermal fuse in the cabinet
- 2 x PG9 cable gland
- Robust, plastic-coated aluminium cabinet with front protective grille
- The speaker complies with British Standard BS 5839, part 8
- Supplied with plastic wall bracket for pivoting and tilting

TECHNICAL SPECIFICATIONS

TS-C10-300/T

Active/passive	passive
Transmission technology	100 V

TS-C10-300/T

Power rating (RMS)	10/6/3/1.5 W
Frequency range	200-18,000 Hz
Full range speaker	2 x 77 mm
Number of speakers	2
SPL	95 dB/W/m
Max. rated SPL	104 dB
Radiation angle/beam angle	H: 149°/V: 66°
Radiation angle, horizontal	149°
Radiation angle, vertical	66°
Housing material	aluminium
Colour	white aluminium, RAL 9006
Mounting device	wall bracket
Protection class	IP66
Admiss. ambient temp.	-20 °C to +90 °C
Dimensions	100 x 296 x 92 mm
Width	100 mm
Height	296 mm
Depth	92 mm
Weight	1.6 kg
Packing dimensions (W x H x L)	0.175 x 0.19 x 0.37 m
Gross weight	2.06 kg
Net weight	1.758 kg