



EDL-36TW

Order No.: 0162070

PRODUCTINFOS

PA ceiling speaker,

for a high safety level in case of a fire.

- 100 V transmission technology
- Additional integrated tweeter
- Fire protection cover
- Metal housing with fitted ceramic terminal
- Thermal fuse: 1 A/150 °C, for disconnecting a faulty speaker in case of a short circuit (fire), so that the function of one speaker line is maintained
- 3-step power selector switch
- Earth connection
- Glass fibre insulated supply line with high-strength cable gland
- Quick-mounting facility
- For a ceiling thickness from 2 to 40 mm

TECHNICAL SPECIFICATIONS

EDL-36TW

Transmission technology	100 V
Frequency range	150-20,000 Hz
Power rating (RMS)	10/5/2.5 W
SPL	95 dB/W/m
Mounting cutout	Ø 190 mm
Mounting depth	90 mm
Dimensions	Ø 200 mm x 100 mm
Outside diameter	Ø 200 mm
Width	Ø 200 mm
Depth	100 mm
Colour	white
Admiss. ambient temp.	0-40 °C
Weight	1.45 kg
Packing unit	1
Type of speaker	165
Packing dimensions (W x H x L)	0.23 x 0.14 x 0.23 m
Gross weight	1.747 kg
Net weight	1.451 kg