



EDL-42HQ

Order No.: 0163890

PRODUCTINFOS

Hi-fi wall and ceiling speaker, 15 W

- 100 V transmission technology or 8 Ω operation
- Power taps: 100 V (8/4/2/1 W)
- 2-way version with coaxial dome tweeter
- 10 cm (4") bass speaker with waveguide and 20 mm (3/4") silk dome
- Excellent sound characteristics
- Supplied with 2 stylish protective metal grilles for an individual look
- Protective grille to be magnetically attached
- For a wall thickness/ceiling thickness from 8 to 30 mm

TECHNICAL SPECIFICATIONS

EDL-42HQ

Impedance (Z)	8 Ω
Transmission technology	100 V or low-impedance
Frequency range	70-20,000 Hz

EDL-42HQ

Resonant frequency (fs)	70 Hz
Power rating (RMS)	15 W (8 Ω) 8/4/2/1 W (100 V)
Peak music power output (MAX)	30 W
SPL	85 dB/W/m
Max. rated SPL	96 dB
Mounting cutout	Ø 141 mm
Mounting depth	70 mm
Dimensions	Ø 158 mm x 72 mm
Outside diameter	Ø 158 mm
Width	Ø 158 mm
Depth	70 mm
Colour	white
Admiss. ambient temp.	0-40 °C
Weight	0.930 kg
Packing unit	1
Type of speaker	100
Packing dimensions (W x H x L)	0.174 x 0.085 x 0.174 m
Gross weight	1.08 kg
Net weight	0.945 kg

EDL-42HQ

Front grille	metal/plastic
--------------	---------------