



ESP-22/WS

Order No.: 0161670

PRODUCTINFOS

PA hi-fi wall and ceiling speaker

- 100 V transmission technology
- 2-way version with pivoting dome tweeter
- Plastic housing with protective metal grille
- ABS plastic material, self-extinguishing according to UL 94V-0
- Excellent sound characteristics
- For a wall thickness/ceiling thickness from 8 to 35 mm

TECHNICAL SPECIFICATIONS

ESP-22/WS

| | |
|-------------------------|------------------|
| Transmission technology | 100 V |
| Frequency range | 50-20,000 Hz |
| Power rating (RMS) | 20/15/10/5/2.5 W |
| SPL | 88 dB/W/m |
| Mounting cutout | 275 x 190 mm |

ESP-22/WS

| | |
|----------------------------------|----------------------|
| Mounting depth | 90 mm |
| Dimensions | 306 x 220 x 100 mm |
| Width | 306 mm |
| Height | 220 mm |
| Depth | 100 mm |
| Colour | white |
| Admiss. ambient temp. | 0-40 °C |
| Weight | 2.6 kg |
| Packing unit | 1 |
| Type of speaker | 165 |
| Packaging dimensions (W x H x L) | 0.27 x 0.13 x 0.35 m |
| Gross weight | 2.955 kg |
| Net weight | 2.585 kg |

ESP-22/WS

| | |
|------------|---------------|
| EAN code | 4007754176131 |
| Net weight | 2.585 kg |