



## ESP-8U



Order No.: 0162170

### PRODUCTINFOS

#### PA wall and ceiling speaker for flush mounting

- 100 V line technique via audio transformer with 3 power taps
- Perfect sound presence for a powerful voice reproduction with a very high audibility
- 20 cm speaker of very sensitivity (99 dB/W/m)
- Plastic tray for flush mounting in walls or solid ceilings
- Required hole in wall: approx. 242 x 242 x 100 mm
- Metal front grille with plastic frame

### TECHNICAL SPECIFICATIONS

#### ESP-8U

|                         |               |
|-------------------------|---------------|
| Transmission technology | 100 V         |
| Frequency range         | 200-17,000 Hz |
| Power rating (RMS)      | 6/3/1.5 W     |
| SPL                     | 99 dB/W/m     |
| Mounting cutout         | 242 x 242 mm  |

**ESP-8U**

|                                |                         |
|--------------------------------|-------------------------|
| Mounting depth                 | 100 mm                  |
| Dimensions                     | 248 x 248 x 100 mm      |
| Width                          | 248 mm                  |
| Height                         | 248 mm                  |
| Depth                          | 100 mm                  |
| Colour                         | white/black             |
| Admiss. ambient temp.          | 0-40 °C                 |
| Weight                         | 1.7 kg                  |
| Packing unit                   | 1                       |
| Type of speaker                | 200                     |
| Packing dimensions (W x H x L) | 0.255 x 0.115 x 0.255 m |
| Gross weight                   | 1.86 kg                 |
| Net weight                     | 1.69 kg                 |