



ESUB-6C/WS

Order No.: 0259340

Price upon request

PRODUCTINFOS

Flush-mount wall and ceiling PA subwoofer, 55 W

- Band-pass subwoofer with 16 cm (6") speaker of long excursion
- 100 V line technique with 4 power taps
- Switchable to 4 Ω
- Supplied with UL-certified safety rope as additional mounting safeguard for the subwoofer
- Robust ceramic connecting terminal
- Integrated crossover network
- For a ceiling thickness from 5 to 32 mm

TECHNICAL SPECIFICATIONS

ESUB-6C/WS

Impedance (Z)	4 Ω
Transmission method	100 V
Frequency range	45-280 Hz

ESUB-6C/WS

Power rating (RMS)	40/20/10 W (100 V), 55 W (4 Ω)
Peak music power output (MAX)	110 W
Sensitivity	88 dB/W/m
Max. rated SPL	104 dB
Radiation angle	180°
Radiation angle, horizontal	180°
Radiation angle, vertical	180°
Mounting cutout	Ø 268 mm
Mounting depth	255 mm
Dimensions	Ø 310 mm x 265 mm
Outside diameter	Ø 310 mm
Width	Ø 310 mm
Depth	265 mm
Admiss. ambient temp.	0-40 °C
Weight	5 kg
Packing unit	1
Type of speaker	165