



IT-33

Order No.: 0162190

PRODUCTINFOS

Weatherproof horn speaker

- 100 V line technique
- IP54 tested
- White ABS housing (self-extinguishing, complies with standard UL 94V-0)
- Particularly high power capability in relation to its size
- Suitable for general indoor and outdoor applications
- Integrated high-pass filter for optimising the sound and stability

TECHNICAL SPECIFICATIONS

IT-33

Active/passive	passive
Transmission technology	100 V
Total power rating	25 W
Power rating (RMS)	25/12.5/6.25 W
Frequency range	500-13,000 Hz

IT-33

Number of speakers	1
SPL	107 dB/W/m
Radiation angle/beam angle	H: 90°/V: 90°
Radiation angle, horizontal	90°
Radiation angle, vertical	90°
Features	integrated high-pass filter
Housing material	ABS, UL 94V-0
Colour	white
Mounting device	mounting bracket
Protection class	IP54
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	Ø 130 mm x 175 mm
Width	Ø 130 mm
Depth	175 mm
Weight	1.8 kg
Other features	weatherproof
Packing dimensions (W x H x L)	0.155 x 0.22 x 0.155 m
Gross weight	1.915 kg
Net weight	1.795 kg