



## IT-60

Order No.: 0162990

### PRODUCTINFOS

#### Weatherproof horn speaker,

with high power capability.

- 100 V line technique
- Weatherproof and IP66 tested
- Protected against powerful water jets
- Suitable for general indoor and outdoor applications
- Light grey ABS housing (self-extinguishing, complies with standard UL 94V-0)
- Supplied with stainless steel mounting bracket
- Integrated ceramic connection terminal with thermal fuse
- 4 power taps

### TECHNICAL SPECIFICATIONS

#### IT-60

Active/passive	passive
Transmission technology	100 V

**IT-60**

Total power rating	60 W
Power rating (RMS)	60/30/15/7.5 W
Frequency range	230-9,000 Hz
Number of speakers	1
SPL	110 dB/W/m
Radiation angle/beam angle	H: 80°/V: 80°
Radiation angle, horizontal	80°
Radiation angle, vertical	80°
Features	thermal fuse
Housing material	ABS, UL 94V-0
Colour	light grey
Mounting device	stainless steel mounting bracket
Protection class	IP66
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	Ø 305 mm x 385 mm
Width	Ø 305 mm
Depth	385 mm
Weight	4 kg
Inputs	4 power taps
Other features	weatherproof
Packing dimensions (W x H x L)	0.32 x 0.43 x 0.32 m
Gross weight	4.92 kg
Net weight	4.04 kg