



## ESP-232/WS

Order No.: 0162610

### PRODUCTINFOS

#### Weatherproof 2-way PA wall-mount speaker system

- 100 V PA speaker system with an excellent sound
- 13 cm polypropylene bass-midrange speaker and dome tweeter
- 4 power taps
- Power selector switch with 8  $\Omega$  operating position
- Excellent efficiency for a speaker of such a compact size
- Available in black (SW) or white (WS) plastic with respectively lacquered aluminium grille, modern design
- Supplied with matching metal wall brackets

### TECHNICAL SPECIFICATIONS

#### ESP-232/WS

Active/passive	passive
Transmission technology	100 V or low-impedance
Total power rating	50 W

**ESP-232/WS**

	30/20/10/5 W (100 V)
Power rating (RMS)	
	25 W (8 $\Omega$ )
Impedance	8 $\Omega$
Frequency range	75-20,000 Hz
Number of speakers	2
Speaker size	13 cm (5")
SPL	89 dB
Radiation angle/beam angle	H: 120°/V: 100°
Radiation angle, horizontal	120°
Radiation angle, vertical	100°
Housing material	plastic
Colour	white
Mounting device	mounting bracket
Protection class	IP55
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	160 x 260 x 180 mm
Width	160 mm
Height	260 mm
Depth	180 mm
Weight	2.3 kg
Inputs	spring-load. speaker term.
Packaging dimensions (W x H x L)	0.205 x 0.19 x 0.3 m
Gross weight	2.8 kg
Net weight	2.44 kg