



## WALL-05DTM/WS

Order No.: 1000788

### PRODUCTINFOS

The wall speaker WALL-05DTM/WS features an integrated 1-channel Dante® module. This Dante® speaker is particularly suitable for commercial applications in the professional field. It can be used for applications where several audio channels have to be transmitted over great distances and to different areas or locations. The fields of application include schools, office buildings, fitness centres, shops and restaurants. Compared with analogue transmission, digital transmission provides several benefits. The quality of the cable is not required to be as high as with analogue transmissions and even with greater distances, the signal features a comparably low susceptibility to interference.

Compared with other Audio over Ethernet applications, e.g. CobraNet or EtherSound, Dante® features integrated gigabit support, more channels, a lower latency and automatic configuration.

The power for WALL-05DTM/WS is supplied via PoE (Power over Ethernet) or optionally via a power supply (19 V/2.5 A).

#### Active speaker with integrated Dante® module

- 2-way system
- 13 cm (5") bass-midrange speaker and 13 mm (½") tweeter
- Mounting bracket for pivoting and tilting
- Power supply via PoE (Power over Ethernet) or via optional power supply (19 V/2.5 A)

System requirements Dante®: Windows 7/8.1/10/11 or MacOS 10.9.5/10.10.5/10.11

The brand Dante® as well as the Dante® software which may have been integrated into these products are licenced by Audinate Pty Ltd.

## TECHNICAL SPECIFICATIONS

### WALL-05DTM/WS

Active/passive	active
Transmission technology	Dante®
Power rating (RMS)	30 W
Frequency range	62-20,000 Hz
System	2-way
Bass speaker	13 cm (5") bass-midrange speaker
Tweeter	13 mm (½") tweeter
Number of speakers	2
Speaker size	13 cm
SPL	89 dB/W/m
Max. rated SPL	105 dB
Housing material	plastic
Colour	white
Mounting device	mounting bracket, for pivoting and tilting
Admiss. ambient temp.	0-40 °C
Power supply	PoE or power supply 19 V/2.5 A (not supplied)
Dimensions	163 x 252 x 165 mm
Width	163 mm
Height	252 mm
Depth	165 mm
Weight	2.12 kg
Inputs	1 x RJ45 (Dante® IN)
Outputs	1 x RJ45 (feed-through output)
Packing dimensions (W x H x L)	0.31 x 0.275 x 0.225 m
Gross weight	2.72 kg
Net weight	2.44 kg