



WALL-05SET/WS

Order No.: 0130132

PRODUCTINFOS

Active 2-way stereo speaker system, 2 x 30 W

- Set consists of one active and one passive speaker system. Connection of the passive system to the active system via screw terminal strip
- Active speaker system with integrated 2-channel amplifier
- Stereo RCA input or balanced input L/R via screw terminal strip
- Volume control and 2-way tone control
- Auto standby
- 13 cm (5") bass speaker system and dome tweeter
- Stylish white plastic cabinet
- Mounting bracket for pivoting and tilting

TECHNICAL SPECIFICATIONS

WALL-05SET/WS

Active/passive	active/passive
Transmission technology	cable
Total output power	2 x 50 W

WALL-05SET/WS

Power rating (RMS)	2 x 30 W
Frequency range	80-20,000 Hz
Input signal	500 mV/20 k Ω (unbal.) 660 mV/40 k Ω (bal.)
System	2-way
Bass speaker	13 cm (5") bass speaker
Tweeter	dome tweeter
Number of speakers	2
Speaker size	13 cm (5")
SPL	89 dB/W/m
Max. rated SPL	104 dB
Radiation angle/beam angle	H: 110°/V: 90°
Radiation angle, horizontal	110°
Radiation angle, vertical	90°
Housing material	plastic
Colour	white
Mounting device	mounting bracket
Admiss. ambient temp.	0-40 °C
Power supply	~ 230 V/50 Hz/100 VA
Dimensions	163 x 252 x 203 mm (with bracket)
Width	163 mm
Height	252 mm
Depth	203 mm
Weight	5.5 kg (pair)
Inputs	1 x RCA L/R (unbal.) 1 x terminal L/R (bal.) spring-load. speaker term. (passive speaker system) spring-load. speaker term.
Other features	pair
Packaging dimensions (W x H x L)	0.2 x 0.28 x 0.425 m
Gross weight	6.9 kg
Net weight	5.63 kg