



WALL-06SET/WS

Order No.: 0130131

PRODUCTINFOS

Active 2-way stereo speaker system, 2 x 30 W

- Set consists of one active and one passive speaker system. Connection of the passive system to the active system via screw terminal strip
- Active speaker system with integrated 2-channel amplifier
- Stereo RCA input or balanced input L/R via screw terminal strip
- Volume control and 2-way tone control
- Auto standby
- Built-in power supply with 3-pole IEC jack
- 16 cm (6") bass speaker system and dome tweeter
- Stylish white plastic cabinet
- Mounting bracket for pivoting and tilting

TECHNICAL SPECIFICATIONS

WALL-06SET/WSActive/passiveTransmission technologycable





WALL-06SET/WS - Page: 2

WALL-06SET/WS

Total output power	2 x 50 W
Power rating (RMS)	2 x 30 W
Frequency range	70-20,000 Hz
Input signal	890 mV/20 kΩ (unbal,.) 1,600 mV/40 kΩ (bal.)
System	2-way
Bass speaker	16 cm (6") bass speaker
Tweeter	dome tweeter
Number of speakers	2
Speaker size	16 cm (6")
SPL	90 dB/W/m
Max. rated SPL	105 dB
Housing material	plastic
Colour	white
Mounting device	mounting bracket
Admiss. ambient temp.	0-40 °C
Power supply	~ 230V/50 Hz/140VA
Dimensions	196 x 303 x 250 mm (with bracket)
Width	196 mm
Height	303 mm
Depth	250 mm
Weight	8 kg (pair)
Inputs	1 x RCA L/R (unbalanced) 1 x terminal L/R (balanced) spring-load. speaker term. (passive speaker system) spring-load. speaker term.
Other features	pair
Packing dimensions (W x H x L)	0.23 x 0.33 x 0.505 m
Gross weight	8.65 kg
Net weight	8 kg