



ETS-8060TW/WS

Order No.: 0163780

PRODUCTINFOS

PA hi-fi column speaker

- High-quality 2-way column speaker with excellent sound characteristics
- 100 V line technique or 8 Ω operation
- 4 x 5 cm (2") full range speaker with paper cone
- 25 mm (1") centrally arranged dome tweeter
- 3 power taps: 20/10/5 W
- Power capability: 40 W in 8 Ω operation
- Connection is made via cable with high-strength cable gland (length: 2 m)
- Robust aluminium cabinet of an appealing design with cloth-covered plastic front protective grille
- Supplied with pivoting and tiltable wall bracket

TECHNICAL SPECIFICATIONS

ETS-8060TW/WS

Active/passive	passive
Transmission method	100 V

ETS-8060TW/WS

Power rating (RMS)	20/10/5 W (100 V) 40 W (8 Ω)
Impedance	8 Ω
Frequency range	160-20,000 Hz
Full range speaker	4 x Ø 50 mm
Tweeter	1
Number of speakers	5
Sensitivity	89 dB/W/m
Max. rated SPL	107 dB
Beam angle	H: 180°/V: 40°
Radiation angle, horizontal	180°
Radiation angle, vertical	40°
Housing material	aluminium
Colour	white
Mounting device	wall bracket
Admiss. ambient temp.	0-40 °C
Dimensions	85 x 430 x 70 mm
Width	85 mm
Height	430 mm
Depth	70 mm
Weight	2.5 kg
Inputs	cable
Packing dimensions (W x H x L)	0.17 x 0.15 x 0.51 m
Gross weight	2.56 kg
Net weight	2.2 kg