



MKS-64/WS

Order No.: 0131140

PRODUCTINFOS

Pair of 2-way speaker systems, 60 W, 4 Ω

- Dome tweeter
- Excellent sound quality
- Black (SW) or white (WS) plastic cabinet
- Pivoting mounting bracket
- Bevelled shape of cabinets also allows mounting in corners

Pair of 2-way speaker systems, 60 W, 4 Ω

- The pair of 2-way speaker systems with dome tweeter features an excellent sound quality
- Supplied with pivoting mounting bracket
- Bevelled shape of cabinets also allows mounting in corners

Specifications:

Active/passive: passive

Impedance: 4 Ω

Frequency range: 60-20,000 Hz
System: 2-way
Bass speaker: bass speaker
Tweeter: dome tweeter
Number of speakers: 2
Power rating: 60 W
Peak music power output: 90 W
Sensitivity: 89 dB/W/m
Max. rated SPL: 106 dB
Housing material: plastic
Colour: white
Mounting device: 2 x M6 thread
Admiss. ambient temp.: 0-40 °C
Width: 215 mm
Height: 290 mm
Depth: 172 mm
Weight: 3.4 kg
Inputs: spring-load. speaker term.

TECHNICAL SPECIFICATIONS

MKS-64/WS

Active/passive	passive
Total power rating	90 W
Power rating (RMS)	60 W
Impedance	4 Ω
Frequency range	60-20,000 Hz
System	2-way
Bass speaker	bass speaker
Tweeter	dome tweeter
Number of speakers	2
SPL	89 dB/W/m
Max. rated SPL	106 dB
Housing material	plastic
Colour	white
Mounting device	2 x thread M6
Admiss. ambient temp.	0-40 °C
Dimensions	215 x 290 x 172 mm
Width	215 mm
Height	290 mm

MKS-64/WS

Depth	172 mm
Weight	3.4 kg
Inputs	spring-load. speaker term.
Packing dimensions (W x H x L)	0.27 x 0.36 x 0.44 m
Gross weight	7.54 kg
Net weight	6.876 kg