



MOVE-10PMK2

Order No.: 1000226

PRODUCTINFOS

Professional PA speaker system, 350 W, 8 Ω

- Compact professional full range bass-reflex system
- Cabinet made of birch plywood
- 25 cm (10", FaitalPro 10PR300) bass speaker
- 25 mm (1", 44 mm voice coil, Celestion CDX1-1747) horn tweeter, can be turned by 90°
- Switchable between passive operation and bi-amp active operation
- Neutral sound tuning
- 'Catch & Carry' carrying handle
- M8 threaded inserts for suspended installation
- 2 x NEUTRIK SPEAKON terminal, in/out
- Stand sleeve, robust front grille
- Ball-proof acc. to DIN 18032, Part 3

TECHNICAL SPECIFICATIONS

MOVE-10PMK2

Active/passive passive

MOVE-10PMK2

Transmission technology	cable
Total power rating	700 W
Power rating (RMS)	350 W
Impedance	8 Ω
Frequency range	55-20,000 Hz
System	2-way bass-reflex
Bass speaker	25 cm (10", FaitalPro 10PR300)
Tweeter	dyn. 25 mm mid-high range speaker (1", 44 mm voice coil, Celestion CDX1-1747)
Number of speakers	2
Speaker size	25 cm (10")
SPL	96 dB/W/m
Max. rated SPL	121 dB
Radiation angle/beam angle	H: 80°/V: 40°, horn can be turned by 90°
Radiation angle, horizontal	80°
Radiation angle, vertical	40°
Housing material	birch plywood
Colour	black
Admiss. ambient temp.	0-40 °C
Dimensions	320 x 545 x 350 mm
Width	320 mm
Height	545 mm
Depth	350 mm
Weight	13.9 kg
Inputs	1 x NEUTRIK SPEAKON
Outputs	1 x NEUTRIK SPEAKON par. out
Accessories	MOVE-10/BAG
Packing dimensions (W x H x L)	0.32 x 0.545 x 0.35 m
Gross weight	14.48 kg
Net weight	13.9 kg