



PAB-52WP/WS

Order No.: 0253580

PRODUCTINFOS

Weatherproof PA speakers with IP classification.

Exactly the right speakers whenever a high sound quality, a high volume capability and a respective resistance to all weather conditions are required. Ideally suited for permanent open-air applications, e.g. at fairground attractions, PA applications in pedestrian areas, at sports facilities and wherever a weather-protected installation of the speakers is not possible.

Weatherproof high-performance PA speaker system, 50 W

- Compact wideband bass-reflex system in an ABS cabinet
- 100 V or 4 Ω operation, selectable
- 13 cm (5") high-quality full range speaker with aluminium cone
- Excellent sound characteristics
- Front grille with water-repellent gauze
- Recessed connection terminal with cover plate and high-strength cable gland
- Metal parts and wall bracket made of stainless steel
- Ball-proof according to DIN 18032, Part 3

"The cabinets give a solid impression ... and meet IP45 requirements. All four speaker systems are suitable for pleasant background music ... the large PAB-8WP/WS is capable of quite high volume levels ... however, the small ones should not be underestimated ... these speaker systems are impressive and the price is quite reasonable for weatherproof speaker systems."

TECHNICAL SPECIFICATIONS

PAB-52WP/WS

Active/passive	passive
Transmission technology	100 V
Power rating (RMS)	50/25/12.5 W
Impedance	4 Ω
Frequency range	60-18,000 Hz
System	wideband bass-reflex
Full range speaker	13 cm (5") full range speaker
Number of speakers	1
Speaker size	13 cm (5")
SPL	87 dB/W/m
Max. rated SPL	104 dB
Housing material	ABS
Colour	white
Mounting device	mounting bracket
Protected against ball rebound	yes
Protection class	IP45
Admiss. ambient temp.	-10 °C to +40 °C
Dimensions	200 x 200 x 190 mm
Width	200 mm
Height	200 mm
Depth	190 mm
Weight	5.1 kg
Inputs	screw terminal
Packing dimensions (W x H x L)	0.25 x 0.29 x 0.23 m
Gross weight	6 kg
Net weight	5.46 kg