



PAB-68/WS

Order No.: 0131940

PRODUCTINFOS

This particularly attractive and efficient series of PA speaker systems

is clearly designed for effective fixed installations, whether in restaurants and bars, hotels, for background PA applications at sport facilities, PA applications in adjoining rooms at discotheques or at conferences: these PAB speaker systems offer a perfect price-performance ratio and a high quality.

Pairs of high-quality PA speakers, 40 W, 8 Ω

- 2-way speaker systems in an ABS cabinet which is both functional and at the same time of an attractive appearance, bass-reflex
- Polypropylene bass speaker and dome tweeter with horn front attachment (waveguide)
- High-quality crossover networks
- Very well-balanced and clear sound which also impresses with a genuine reproduction of vocals and demanding music
- LED at the front for indicating the level
- Supplied with wall bracket

TECHNICAL SPECIFICATIONS

PAB-68/WS

Active/passive	passive
Total power rating	70 W
Power rating (RMS)	40 W
Impedance	8 Ω
Frequency range	55-22,000 Hz
System	2-way
Bass speaker	polypropylene bass speaker
Tweeter	dome tweeter
Number of speakers	2
Sensitivity	90 dB/W/m
Max. rated SPL	106 dB
Housing material	ABS plastic
Colour	white
Mounting device	2 x thread M6
Admiss. ambient temp.	0-40 °C
Dimensions	210 x 350 x 200 mm
Width	210 mm
Height	350 mm
Depth	200 mm
Weight	3.9 kg
Inputs	speaker screw terminal
Packing dimensions (W x H x L)	0.24 x 0.37 x 0.515 m
Gross weight	8.62 kg
Net weight	7.88 kg