



20W

RBT-56

Order No.: 0013210

PRODUCTINFOS

Hi-fi ribbon tweeter, 10 W, 4 Ω

- Magnetostatic tweeter of compact size
- Neodymium magnet system
- Fine and brilliant reproduction of the high frequencies
- Round cone with Kapton and aluminium film
- For use from 5,000 Hz on
- Plastic sound diffuser panel (front)

TECHNICAL SPECIFICATIONS

RBT-56

Impedance (Z)	4 Ω
Frequency range	5,000-40,000 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	5,000 Hz
Power rating (RMS)	10 W
Peak music power output (MAX)	20 W

RBT-56

SPL	90 dB/W/m
DC resistance (Re)	3.5 Ω
Mounting cutout	Ø 40 mm
Mounting depth	10 mm
Mounting hole diameter	Ø 48 mm
Dimensions	56.5 mm
Outside diameter	Ø 56.5 mm
Width	Ø 56.5 mm
Depth	10 mm
Colour	black
Admiss. ambient temp.	0-40 °C
Weight	0.035 kg
Packing unit	1
Packing dimensions (W x H x L)	0.065 x 0.015 x 0.075 m
Gross weight	0.045 kg
Net weight	0.035 kg