



## SUB-10

Order No.: 0259875

### PRODUCTINFOS

#### **This 25 cm (10") passive subwoofer**

has been developed to deliver a powerful bass reproduction from compact cabinets and features a power rating of 500 W max. The band-pass cabinet with its 10" bass speaker of long excursion generates a dry and deep bass. It can be used as subwoofer support for PA systems in restaurants and bars or shops to ensure a rich and powerful sound. Nevertheless, it can also be used as an additional subwoofer for smaller PA speakers and simply be connected in parallel due to the integrated crossover network (low-pass filter at approx. 200 Hz).

#### **Passive subwoofer, 500 W/8 Ω**

- Band-pass subwoofer with double ventilation
- 1 x 25 cm (10") top-class woofer
- Slimline and compact design for upright and horizontal setup
- High-quality lacquered cabinet made of plywood, front grille with inner lining
- Integrated crossover network (low-pass) with crossover frequency at 200 Hz
- 4 x M8 lateral threaded insert as installation aid
- Speakers connected to the subwoofer in parallel must have a nominal impedance of 8 Ω min.
- Stand sleeve at the top

## TECHNICAL SPECIFICATIONS

### SUB-10

Active/passive	passive
Transmission technology	cable
Total power rating	500 W
Power rating (RMS)	250 W
Impedance	8 $\Omega$
Frequency range	40-200 Hz
System	band-pass subwoofer
Bass speaker	1 x 25 cm (10")
Number of speakers	1
Speaker size	25 cm (10")
SPL	92 dB/W/m
Max. rated SPL	116 dB
Radiation angle/beam angle	omnidirectional
Housing material	multiplex
Colour	black
Mounting device	threaded inserts
Admiss. ambient temp.	0-40 °C
Dimensions	300 x 610 x 410 mm
Width	300 mm
Height	610 mm
Depth	410 mm
Weight	19.84 kg
Inputs	1 x NEUTRIK SPEAKON, speaker terminals
Packing dimensions (W x H x L)	0.42 x 0.74 x 0.53 m
Gross weight	23.66 kg
Net weight	19.84 kg