



## WALL-04T/WS

Order No.: 0163570

### PRODUCTINFOS

#### Pair of 2-way PA speaker systems

- 100 V wall speaker with plastic cabinet in white
- 4 power taps as well as switchable to 8  $\Omega$  operation
- 10 cm (4") bass-midrange speaker and 12 mm ( $\frac{1}{2}$ ") dome tweeter
- High sound quality and speech intelligibility
- Mounting bracket for pivoting and tilting
- Connecting terminal with cover

#### Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG  
Zum Falsch 36  
28307 Bremen  
Germany  
info@monacor.com

## TECHNICAL SPECIFICATIONS

### WALL-04T/WS

Active/passive	passive
Transmission technology	100 V or low-impedance
Total power rating	60 W
Power rating (RMS)	16/8/4/2 W (100 V) 30 W (8 $\Omega$ )
Impedance	8 $\Omega$
Frequency range	90-20,000 Hz
System	2-way
Bass speaker	10 cm (4") bass-midrange speaker
Tweeter	12 mm (½") dome tweeter
Number of speakers	2
Speaker size	10 cm (4")
SPL	87 dB/W/m
Max. rated SPL	100 dB
Radiation angle/beam angle	H: 120°/V: 100°
Radiation angle, horizontal	120°
Radiation angle, vertical	100°
Housing material	plastic
Colour	white
Mounting device	mounting bracket
Protection class	IP65
Admiss. ambient temp.	0-40 °C
Dimensions	130 x 197 x 164 mm (with bracket)
Width	130 mm
Height	197 mm
Depth	164 mm
Weight	1.8 kg
Inputs	spring-load. speaker term.
Other features	for pivoting and tilting
Packaging dimensions (W x H x L)	0.155 x 0.22 x 0.33 m
Gross weight	3.82 kg
Net weight	3.51 kg

### WALL-04T/WS

EAN code	4007754261240
Net weight	3.51 kg

