



WALL-05T/WS

Order No.: 0163590

PRODUCTINFOS

Pair of 2-way PA speaker systems

- Wall speaker with plastic cabinet in white
- 4 power taps as well as switchable to 8 Ω operation
- 13 cm (5") bass-midrange speaker and 12 mm (½") dome tweeter
- High sound quality and speech intelligibility
- Mounting bracket for pivoting and tilting
- Connecting terminal with cover

TECHNICAL SPECIFICATIONS

WALL-05T/WS

Active/passive	passive
Transmission technology	100 V
Total power rating	80 W
Power rating (RMS)	16/8/4/2 W (100 V) 40 W (8 Ω)

WALL-05T/WS

Impedance	8 Ω
Frequency range	80-20,000 Hz
System	2-way
Bass speaker	13 cm (5") bass-midrange speaker
Tweeter	12 mm (½") dome tweeter
Number of speakers	2
Speaker size	5"
SPL	89 dB/W/m
Max. rated SPL	104 dB
Housing material	plastic
Colour	white
Mounting device	mounting bracket
Protection class	IP65
Admiss. ambient temp.	0-40 °C
Dimensions	163 x 252 x 203 mm (with bracket)
Width	163 mm
Height	252 mm
Depth	203 mm
Weight	2.6 kg
Inputs	spring-load. speaker term.
Other features	for pivoting and tilting
Packing dimensions (W x H x L)	0.2 x 0.28 x 0.425 m
Gross weight	5.73 kg
Net weight	5.24 kg