



EDL-110/WS

Order No.: 0161930

PRODUCTINFOS

Weatherproof PA sound projector

- 100 V transmission technology
- 1 speaker with polypropylene cone
- Splashproof due to plastic housing with rubber seals and high-strength cable gland
- Connection cable with 3 power taps
- Stainless steel screws and pivoting mounting bracket

TECHNICAL SPECIFICATIONS

EDL-110/WS

Active/passive	passive
Transmission technology	100 V
Total power rating	10 W
Power rating (RMS)	10/5/2.5 W
Frequency range	120-20,000 Hz
Number of speakers	1

EDL-110/WS

Speaker size	16 cm (6.5")
SPL	94 dB/W/m
Radiation angle/beam angle	110°
Radiation angle, horizontal	110°
Radiation angle, vertical	110°
Housing material	plastic
Colour	white
Mounting device	mounting bracket
Protection class	IP44
Admiss. ambient temp.	-30 °C to +40 °C
Dimensions	Ø 180 mm x 270 mm
Width	Ø 180 mm
Height	Ø 180 mm
Depth	270 mm
Weight	2 kg
Inputs	connection cable with 3 power taps
Packaging dimensions (W x H x L)	0.24 x 0.305 x 0.275 m
Gross weight	2.5 kg
Net weight	2.08 kg