



EDL-220/WS

Order No.: 0161950

PRODUCTINFOS

Weatherproof PA sound projector

- 100 V transmission technology
- 2 speakers with polypropylene cone for bilateral radiation
- Splashproof due to plastic housing with rubber seals
- Connection cable with 3 power taps
- Pivoting mounting bracket and screws made of stainless steel

TECHNICAL SPECIFICATIONS

EDL-220/WS

Active/passive	passive
Transmission technology	100 V
Total power rating	20 W
Power rating (RMS)	20/10/5 W
Frequency range	120-20,000 Hz
Number of speakers	2

EDL-220/WS

Speaker size	16 cm (6.5")
SPL	94 dB/W/m
Radiation angle/beam angle	110°
Radiation angle, horizontal	110°
Radiation angle, vertical	110°
Housing material	plastic
Colour	white
Mounting device	mounting bracket
Protection class	IP44
Admiss. ambient temp.	-30 °C to +40 °C
Dimensions	Ø 180 mm x 251 mm
Width	Ø 180 mm
Height	Ø 180 mm
Depth	251 mm
Weight	2.76 kg
Inputs	cable connection
Packaging dimensions (W x H x L)	0.24 x 0.305 x 0.275 m
Gross weight	3.18 kg
Net weight	2.76 kg