



EDL-412/SW

Order No.: 1000620

PRODUCTINFOS

Weatherproof PA ball speaker

- 100 V transmission technology or 8 Ω operation
- Black ABS housing (self-extinguishing, complies with standard UL 94V-0)
- Supplied with 480 cm connection cable and canopy

TECHNICAL SPECIFICATIONS

EDL-412/SW

Active/passive	passive
Transmission technology	100 V or low-impedance
Total power rating	10 W
Power rating (RMS)	10/5/2.5 W
Impedance	8 Ω
Frequency range	160-20,000 Hz
Full range speaker	130 mm (5")

EDL-412/SW

Number of speakers	1
Speaker size	13 cm (5")
SPL	92 dB/W/m
Radiation angle/beam angle	100°
Radiation angle, horizontal	100°
Radiation angle, vertical	100°
Housing material	ABS, UL 94V-0
Colour	black
Mounting device	cable with canopy
Protection class	IP44
Admiss. ambient temp.	-30 °C to +40 °C
Dimensions	Ø 184 mm
Width	Ø 184 mm
Height	Ø 184 mm
Depth	Ø 184 mm
Weight	1.65 kg
Inputs	cable connection
Packaging dimensions (W x H x L)	0.3 x 0.22 x 0.23 m
Gross weight	2 kg
Net weight	1.65 kg